

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
△					△					
△					△					
APPLICABLE STANDARD										
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +85 °C (NOTE 1)			STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C				
	VOLTAGE	/			APPLICABLE CONNECTOR	/				
	CURRENT	/			APPLICABLE CABLE (NOTE 2, 3)	/				
SPECIFICATIONS										
ITEM		TEST METHOD			REQUIREMENTS			QT/AT		
CONSTRUCTION										
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			X X		
MARKING		CONFIRMED VISUALLY.						X X		
REMARKS				DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED		
NOTE 1: INCLUDE THE TEMPERATURE RISING BY CURRENT. NOTE 2: THIS IS A OPTIONAL PART FOR WITHDRAWAL.				<i>S. Tashiro</i> '01.2.15	<i>S. Tashiro</i> '01.2.15	<i>K. Abayama</i> '01.2.15	<i>K. Katayama</i> '01.2.15			
UNLESS OTHERWISE SPECIFIED, REFER TO JIS C 5402.										
NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST X: APPLICABLE TEST										
HRS HIROSE ELECTRIC CO.,LTD.			SPECIFICATION SHEET			PART NO.				
						DF21-20P/40DP-0.6PTB				
CODE NO.(OLD)		DRAWING NO.			CODE NO.			1/1		
CL		ELC4 - 164110			CL 687-1700-0			1/1		

TO

