

Gap Filler 3500LV (Two-Part)


May 2015

PRODUCT DESCRIPTION

Thermally Conductive, Low Outgassing, Liquid Gap Filling Material

FEATURES AND BENEFITS

- Thermal Conductivity: 3.5 W/m-K
- Low volatility for outgassing sensitive applications
- Ultra-conforming with excellent wet-out for low stress interfaces on applications
- 100% solids - no cure by-products



Gap Filler 3500LV is a two-part, high thermal conductivity, liquid gap filling material. This material offers the mechanical property benefits of a silicone material with the additional feature of low outgassing.

The mixed material will cure at room temperature or can be accelerated with the addition of heat.

The liquid approach offers infinite thickness variations with little to no stress to sensitive components during assembly. As cured, Gap Filler 3500LV provides a soft, form-in-place elastomer that is ideal for fragile assemblies or for filling intricate air voids.

Note: To build a part number, visit our website at www.bergquistcompany.com.

TYPICAL PROPERTIES OF GAP FILLER 3500LV

PROPERTY	IMPERIAL VALUE	METRIC VALUE	TEST METHOD
Color / Part A	Blue	Blue	Visual
Color / Part B	White	White	Visual
Viscosity, High Shear (Pa-s) (1)	45	45	ASTM D5099
Density (g/cc)	3.1	3.1	ASTM D792
Mix Ratio	1:1	1:1	—
Shelf Life @ 25°C (months)	5	5	—
PROPERTY AS CURED			
Color	Light Blue	Light Blue	Visual
Hardness (Shore 00) (2)	40	40	ASTM D2240
Heat Capacity (J/g-K)	0.8	0.8	ASTM D1269
Siloxane Content, ΣD ₄ -D ₁₀ (ppm)	40	40	—
Continuous Use Temp (°F) / (°C)	-76 to 392	-60 to 200	—
ELECTRICAL AS CURED			
Dielectric Strength (V/mil)	275	275	ASTM D149
Dielectric Constant (1000 Hz)	8.0	8.0	ASTM D150
Volume Resistivity (Ohm-meter)	10 ¹⁰	10 ¹⁰	ASTM D257
Flame Rating	V-O	V-O	U.L. 94
THERMAL AS CURED			
Thermal Conductivity (W/m-K)	3.5	3.5	ASTM D5470
CURE SCHEDULE			
Working Time @ 25°C (3)	240 min (4 hrs)	240 min (4 hrs)	—
Cure @ 25°C (hrs) (3)	24	24	—
Cure @ 100°C (min) (3)	30	30	—
1) Capillary Viscosity, 1500/sec, Part A and B measured separately. 2) Thirty second delay value Shore 00 hardness scale. 3) Parallel plate rheometer, see reactivity application note.			

TYPICAL APPLICATIONS INCLUDE

- Lighting
- Automotive in-cabin electronics
- Medical electronics
- Industrial controls
- Optics

CONFIGURATIONS AVAILABLE

- Supplied in cartridge or kit form

Disclaimer

Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery. In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office

Reference 0.1