

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION .19  
 © COPYRIGHT 19 BY AMP INCORPORATED. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS						
J	-	P	LTR	DESCRIPTION	ECN	DATE	DWN	APVD
		0		作成 RELEASED	FJ00-0158-98	30 JAN 98	ES	

NOTE,

- 1 APPLICABLE P.C.BOARD THICKNESS: 1.6mm
- 2 RECOMMENDED MOUNTING SCREW: 4mmDIA, 6mmLENGTH  
TAPPING SCREW SPECIFIED IN JIS B1115, B1122  
(TIGHTENING TORQUE: 4kgcm MAX)
- 3 THE MATING PLUG HSG P/N; 353112,1123632

注:

- 1 通用プリント基板厚: 1.6mm
- 2 推奨取付ネジ: JIS B1115, B1122 タッピンネジ, ナベ2種  
呼び径4, 長さ6mm (締付トルク 4kgcm以下)
- 3 嵌合相手型番; 353112, 1123632

推奨プリント基板取付け寸法 (公差 ±0.1)  
 (MOUNTING DIMENSIONS FOR P.C. BOARD; TOLERANCE ±0.1)  
 ピッチ公差は累積しないこと (NON ACCUMULATE PITCH TOLERANCE)

緑 (GREEN)	1123630-4
色 (COLOR)	型番 (P/N)

<small>THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.</small>		DWN: <i>E. Sasaki</i> 30 JAN 98 CHK: <i>Z. Takahashi</i> APVD: <i>Z. Takahashi</i>	<b>AMP</b> <small>日本エー・エム・ピー株式会社 Kawasaki, Japan</small>
DIMENSIONS: 単位 純 mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 一般公差 10µ ±0.2 30µ ±0.25 100µ ±0.3 ANGLE: ±0.3°	PRODUCT SPEC 製品規格 108-5452 APPLICATION SPEC 取付適用規格	NAME: .04011 SRS MULTI-LOCK CONN. MK-II 48Pos. CAP ASSY 名称: .04011 シリーズ マルチロック コネクタ MK-II 48極 キャップハウジング アッセンブリ
MATERIAL 材料 HOUSING: PBT ハウジング: PBT CONTACT: BRASS コンタクト: 黄銅	FINISH 仕上 PRE-TIN 錫めつき済	WEIGHT 16.8g	SIZE: A2 CAGE CODE: 00779 DRAWING NO: 1123630 RESTRICTED TO: ---
CUSTOMER DRAWING			SCALE: 2-1 SHEET: 1 OF 1 REV: 0

AMP 1471-9 REV 10/93

参考図面